TEE ONDER - 240HP

SPECIAL FEATURES

- 6 Ton Lifting Capacity
- 240 HP Cummins 6CTA8.3-C240
- Genuine Cummins 2000 hr/2yr Warranty •
- New Engine Inspection by Cummins
- Extra-Large Aluminium RadiatorLong Life Anti Corrosion Coolant
- 4 speed ZF WG 200 Powershift Transmission
- 4 Fwd / 3 Rev Gears with Safety Lock Out
- 38 km/h Road Speed
- Gear Kick Down Function
- 3.5m³ General Purpose Bucket
- Heavy Duty Pallet Forks
- Heavy Duty Hay Forks
- 12 Stud Axles
- Steering Priority Valve
- Hydraulic Pilot Control
- Hydraulic Quick Release Hitch
- Quick Hitch Safety Lock Out
- 3,700 mm Dumping Height
- Float Function
- Auto Level
- 3rd Function Hydraulics

- Hydraulic Hose Protection
- Lincoln SKF Auto Greaser
- Luxurious Extra Large Cab
- Reverse Camera / Reverse Alarm
- FM Radio, Fire Extinguisher,
 Drink Holder & Glass Breaker
- Battery Isolation Switch
- Adjustable Steering Column
- Sound Proofing, Cab Fan & Sun Visor
- Electric Park Brake
- UV Protected Windows
- Australian Standards Air Conditioning
- LED Light Bars Front & Rear
- LED Lights, Blinkers, Hazards & Mirrors
- Excellent Filter Access & Engine Components

Available Extras:

- Numerous Attachments
- Soft Ride
- Rear Rippers
- On Road Package
- UHF
- Registration

Finance Available

JACOB 0427 180 673 Jacob@toughindustrial.com.au AARON 0456 676 700 AARON@TOUGHINDUSTRIAL.COM.AU KAHIL 0400 459 097 Kahil@Toughindustrial.com.au





TECHNICAL SPECIFICATIONS - 6 TON CAPACITY

Peri	form	nan	^
ren	IOH	Iall	Ce

 Rated Load
 6,000 kg

 Overall Weight
 20,000 kg

 Bucket Capacity
 3.5 m³

 Underbelly Clearance
 540 mm

 Max. Dump Height
 3,700 mm

 Max. Dump Reach
 1,600 mm

 Overall Dimension
 Length 8,900 mm

Length 8,900 mm Width 3,000 mm Height 3,510 mm

Engine

Model Cummins 6CTA8.3-C240
Type Turbocharged / Water Cooled
Rated RPM 2,200 rpm
Rated Power 179 kw
Max. Torque

Service Refill Capacities

 Fuel
 300 ltr

 Hydraulic Oil
 260 ltr

 Engine Oil
 19 ltr

 Transmission
 35 ltr

Transmission

Type Powershift Transmission
Gears 4 Forward, 3 Reverse
Working Pressure 16 mpa
Max. Speed 38 km/h

WG200

Drive Axle

Decelerating Mode Planetary reduction Wheel Base 3,450 mm Inner Wheel Tread 1,900 mm Axle Clearance 550 mm

Hydraulic System

 System Working Pressure
 18 mpa

 Boom Lifting Time (max load)
 5.5 Sec

 Lowering Time (empty)
 4.5 Sec


 Dumping Time (empty)
 4.5 Sec


 Working Pressure
 18 mpa

 3rd Function Oil Flow
 180 - 200 lpm

Tyres

Tube Standard (tubeless optional) 26.5-25 (20ply)
Front Tyre Pressure 60 psi
Rear Tyre Pressure 55 psi





\$

Prices exclude GST